

# PETROMAR XC 2000 SERIES

## DESCRIPTION

Petromar XC 2000 SERIES is a 20 BN (base number) oil especially designed for the lubrication of new generation and highly rated trunk piston diesel engines in severe service burning residual fuels. Petromar XC oils are formulated to tolerate contamination with residual fuel, as experienced in some installations, without deterioration of its excellent anti-wear properties and viscosity control while maintaining superior engine cleanliness.

## PROPERTIES

- Exhibits API engine service classification of CF performance
- Provides improved fuel solubility for exceptional engine cleanliness
- Offers improved oxidation resistance and very good viscosity control
- Provides superior protection against piston deposits and ring sticking
- Possesses excellent water shedding characteristics for effective removal of water contaminant by centrifuging

## APPLICATION

- Petromar XC 2000 SERIES is suitable for use in diesel engines using fuels with 1.5% - 2.5% sulfur and requiring 20 BN oil.

## GRADES

- SAE 30 and 40

## AVAILABLE PACKAGES

- Bulk
- 200-liter drum
- 18-liter pail

## TYPICAL CHARACTERISTICS

	2030	2040
Specific Gravity at 15.6°C	0.8974	0.9025
Viscosity at 40°C, cSt	96.6	139.5
Viscosity at 100°C, cSt	11.40	14.70
Viscosity Index	105	105
TBN, mg KOH/g	21	21
Flash Point, COC, °C	240	252
Pour Point, °C	-12	-12