PETROGREASE PREMIUM

DESCRIPTION

PETROGREASE PREMIUM is a high quality, smooth-textured, short-fibered multipurpose lithium soap grease. It is structurally modified to make it superior to other lithium It is suitable for lubricating areases. automotive, industrial, marine and railroad equipment under normal loads. It can tolerate occasional high operating temperatures of up to 160°C or continuous high temperature of 150°C with frequent relubrication.

PROPERTIES

- Excellent resistance to degradation due to oxidation
- Mechanical stability
- High water resistance
- Corrosion-inhibiting property
- Enhanced with lemon scent

TYPE

Lithium soap multipurpose grease

APPLICATION

 Plain and anti-friction bearings in steel mills, paper mills, electric motors and generators, pumps, conveyors, compressors, machine tools, gears and couplings, automotive and marine equipment

GRADES

NLGI No. 2 and 3

AVAILABLE PACKAGES

- 400-lb (181-kg) drum
- 35-lb (16-kg) pail

TYPICAL CHARACTERISTICS

	PREMIUM 2	PREMIUM 3
Appearance, Texture	Uniform/Smooth	Uniform/Smooth
Color, Visual	Yellow	Yellow
Worked Pen. at 25°C, 100g, 5 secs. mm/10		
60 strokes	280	238
Dropping Point, °C	180	180
Tilted Wheel Bearing Test		
Slump Rating	Passes	Passes
Leakage in grams	0.3	0.1
Base oil Viscosity, cSt at 40°C	96	96