

ATF PREMIUM

DESCRIPTION

ATF PREMIUM is a multifunctional fluid for automatic and power-shift transmissions. It is designed to meet the tropical country requirements of General Motors Dexron III, Ford Mercon, Allison C-4, and Caterpillar TO-2

PROPERTIES

- Provides quiet operation and smooth shifting
- Resistant to high temperature oxidation and fluid thickening
- Controlled frictional properties
- Outstanding anti-wear performance
- Protects against harmful attack by corrosive acids
- Provides protection against rusting and corrosion
- Compatibility with commonly used seal materials
- Outstanding hydraulic pump performance

APPLICATIONS

- Automatic transmissions, power steering, hydraulic systems, torque converters in cars, trucks and heavy equipment
- For gearboxes of front-wheel drive cars
- Suitable for use in applications where fluids meeting Dexron III, Mercon, Allison C-4 or Caterpillar TO-2 performance are recommended.

GRADE

- SAE 20

AVAILABLE PACKAGES

- 200-liter drum
- 18-liter pail
- 24 x 1 liter in carton

TYPICAL CHARACTERISTICS

Specific Gravity at 15.6 °C	0.8634
Color, Visual	Red
Viscosity at 40°C, cSt	38.5
Viscosity at 100°C, cSt	7.40
Viscosity Index	161
Flash Point, COC, °C	196