# 2T PREMIUM

# **DESCRIPTION**

2T PREMIUM is a premium quality motorcycle oil recommended for Kawasaki, Suzuki and Yamaha motorcycles as well as other two-stroke gasoline engines.

2T PREMIUM is ideal for those pre-mixing the motorcycle oil in the gasoline.

# **PROPERTIES**

- Better engine protection even at its low recommended dosage, assuring longer engine life
- High detergency that keeps pistons, piston rings, cylinder liners, spark plug and exhaust port clean
- Environment-friendly due to cleaner exhaust emissions
- Economical; for every liter of gasoline, only 25 ml of oil is required as compared to the traditional practice of using 50 ml of oil for every liter of gasoline. This means savings due to a 50% reduction in oil usage
- Recommended to users who prefer adding (pre-mixing) the oil to gasoline during tank fill-up; may also be poured into the oil reservoir of motorcycles with an autolube system

(Minor adjustments must be made on the autolube calibration to benefit from the savings of using a 40:1 fuel to oil ratio).

### **GRADE**

SAE 30

# APPLICATION

- Motorcycles, tricycles, small passenger cars, scooters, lawn mowers, small tractors, chainsaws and other portable equipment powered by two-stroke gasoline engines
- Recommended dosages are:

Fuel	2T Premium
(in liters)	(in ml)
1 liter	25 ml
2 liters	50 ml
3 liters	75 ml
4 liters	100 ml
5 liters	125 ml

### **TYPE**

2-stroke motorcycle oil

# **QUALITY LEVELS**

- API Service TC
- JASO FB+

## **AVAILABLE PACKAGES**

- 200-liter drum
- 18-liter pail
- 24 x 1 liter in carton
- 216 x 50 ml sachet in carton
- 144 x 75 ml sachet in carton

## TYPICAL CHARACTERISTICS

Specific Gravity at 15.6 °C 0.8906 Color, ASTM 3.5 Viscosity at 40 °C, cSt 90.8 Viscosity at 100 °C, cSt 10.60 Viscosity Index 99 TBN, mg KOH/g 2.0 Flash Point, COC, °C 238