

## Product Data Sheet

# 2T POWERBURN

### DESCRIPTION

2T POWERBURN is a superior quality, scented motorcycle oil specially formulated for two-stroke gasoline engines equipped with an autolube system. It can be poured directly into the oil reservoir of the autolube without any adjustment in the autolube system. It can also be added to the gasoline tank during fill-ups.

### PROPERTIES

- Readily blends to form a stable mixture with gasoline
- Contains special detergent additives that prevent spark plug fouling, exhaust port blockage, piston scuffing and ring deposits.
- Environment-friendly; reduces exhaust-smoking tendencies of both new and old engines.
- For every liter of gasoline, 50 ml of oil is recommended whether the oil is added to the oil reservoir or poured into the gasoline tank.
- Enhanced with scent/fragrance

### GRADE

- SAE 30

### APPLICATION

- 2-stroke gasoline engines such as motorcycles, tricycles, small passenger cars, scooters, lawn mowers, small tractors, chainsaws and other portable equipment.
- Recommended dosages are:

Fuel (in liters)	2T Powerburn (in ml)
1 liter	50 ml
2 liters	100 ml
3 liters	150 ml
4 liters	200 ml
5 liters	250 ml

### TYPE

- Two-stroke motorcycle oil

### QUALITY LEVEL

- JASO FB

### AVAILABLE PACKAGES

- 200-liter drum
- 18-liter pail
- 24 x 1 liter in carton
- 60 x 200 ml bottles in carton

### TYPICAL CHARACTERISTICS

Specific Gravity at 15.6 °C	0.8834
Color, ASTM	L2.5
Viscosity at 40 °C, cSt	79.23
Viscosity at 100 °C, cSt	9.88
Viscosity Index	104
TBN, mg KOH/g	0.62
Flash Point. COC, °C	258