

Product Data Sheet

2T ENVIRO

DESCRIPTION

2T ENVIRO is a semi-synthetic, high quality motorcycle oil specially designed and formulated to significantly reduce the heavy visible smoke coming from the exhaust of old and new two-stroke gasoline engines. It can be poured directly into the oil reservoir of the autolube without any adjustment in the autolube system. It can also be added to the gasoline tank during fill-ups.

PROPERTIES

- Contains a special component that significantly reduces the visual smoke of both new and old two-stroke engines for cleaner and more environment-friendly exhaust emissions.
- Contains special detergent additives that provide protection against piston and cylinder scuffing, ring sticking, exhaust blocking, spark plug fouling and excessive deposit formation.
- Readily blends to form a stable mixture with gasoline.
- For every liter of gasoline, 50 ml of oil is recommended whether the oil is added to the oil reservoir or poured into the gasoline tank.

GRADE

- SAE 20

APPLICATION

- Two-stroke gasoline engines such as motorcycles, tricycles, small passenger cars, scooters, lawn mowers, small tractors, chainsaws and other portable equipment.
- Recommended dosages are:

Gasoline (in liters)	2T ENVIRO (in ml)
1 liter	50 ml
2 liters	100 ml
3 liters	150 ml
4 liters	200 ml
5 liters	250 ml

TYPE

- Semi-synthetic two-stroke motorcycle oil

QUALITY LEVEL

- JASO FC

AVAILABLE PACKAGES

- 60 x 200 ml bottles in carton

TYPICAL CHARACTERISTICS

Specific Gravity at 15.6 °C	0.8650
Color, ASTM	L1.0
Scent	Cherry
Viscosity at 40 °C, cSt	47.26
Viscosity at 100 °C, cSt	7.742
Viscosity Index	132
TBN, mg KOH/g	0.87
Flash Point. PM, °C	96