

# Product Data Sheet

---

## GX

---

### DESCRIPTION

---

GX is the highest quality general- purpose type gear lubricant suitable for heavy loads sustained at high speeds and subjected to high torque.

### PROPERTY

---

- Multigrades meet both low and high temperature requirements

### GRADES

---

- Monogrades: SAE 90 and 140
- Multigrades: SAE 80W-90 and 85W-140

### QUALITY LEVELS

---

- API Service GL-5
- MIL-L-2105D

### APPLICATIONS

---

- Hypoid or spiral-bevel gears, limited-slip differentials and transmissions
- Fortified with extreme pressure additives, it is used in certain hypoid or spiral-bevel gears, transmissions or gear boxes and limited-slip differentials of both highway and off-highway vehicles

### AVAILABLE PACKAGES

---

- 200-liter drum
- 18-liter pail

### TYPICAL CHARACTERISTICS

---

	80W-90	85W-140	90	140
Specific Gravity at 15.6°C	0.8991	0.9095	0.9075	0.9171
Flash Point, COC, °C	210	220	210	226
Color, ASTM	3.5	4.5	7.0	7.5
Viscosity at 40°C, cSt	139.5	345.6	203.8	488.7
Viscosity at 100°C, cSt	17.50	33.00	17.52	30.40
Viscosity Index	100	96	92	91

---