

# MOTOR OIL

## DESCRIPTION

MOTOR OIL is cost-effective motor oil suitable for passenger cars running in mild service conditions. It gives the engine protection against sludge, wear and rust.

## PROPERTIES

- Protects engines against low temperature sludge formation and rust
- Provides satisfactory performance in either high speed, over-the-road or stop-and-go service due to good thermal stability
- Excellent detergency
- Low tendency to form carbon deposits

## GRADES

- SAE 30 and 40

## APPLICATIONS

- Gasoline and diesel engines of passenger cars
- Recommended only for short oil drain interval applications

## QUALITY LEVEL

- API Service SD/CC

## AVAILABLE PACKAGES

- 200-liter drums
- 18-liter pails
- 6 x 4 liters in cartons
- 24 x 1 liter in cartons

## TYPICAL CHARACTERISTICS

	30	40
Specific Gravity at 15.6 °C	0.8919	0.8930
Flash Point, COC, °C	232	262
Color, ASTM	3.5	4.0
Kinematic Viscosity at 40°C, cSt	96.10	143.2
Kinematic Viscosity at 100°C, cSt	11.30	14.90
Viscosity Index	104	104
TBN, mg KOH/g	4.7	4.7
Pour Point, °C	-9	-6