

Product Data Sheet

REV-X HD

DESCRIPTION

REV-X HD is a high-detergent engine oil recommended for use in engines operating under mild to moderate service conditions. It is also suitable for passenger-type vehicles such as jeeps, buses, Asian Utility Vehicles (AUVs), and mixed commercial fleets. It provides adequate protection from overheating and engine deposits.

PROPERTY

- Provides satisfactory performance in engines used under mild operating conditions

QUALITY LEVEL

- API Service CC/SD

GRADES

- SAE 10, 30, 40 and 50

APPLICATIONS

- Automotive diesel and gasoline engines under mild operating conditions requiring short drain intervals
- SAE 10 grade can also be used as hydraulic and transmission oil for forklifts and construction equipment

AVAILABLE PACKAGES

- 200-liter drum
- 18-liter pail
- 6 x 4 liters in carton (SAE 30 & 40)
- 24 x 1 liter in carton (SAE 30 & 40)

TYPICAL CHARACTERISTICS

	10	30	40	50
Specific Gravity at 15.6 °C	0.8709	0.8833	0.8979	0.8907
Flash Point, COC, °C	218	232	262	264
Color, ASTM	1.0	3.5	4.0	4.0
Viscosity at 40 °C, cSt	29.62	90.81	159.3	218.3
Viscosity at 100 °C, cSt	5.24	10.93	15.04	18.77
Viscosity Index	108	105	94	96
TBN, mg KOH/g	4.7	4.7	4.7	4.7