PETROGREASE MP

DESCRIPTION

PETROGREASE MP is a good quality lithiumtype multipurpose grease for plain and antifriction bearings found in a wide variety of automotive, farm, industrial and construction equipment.

APPLICATION

 Automotive chassis and wheel bearings, plain and anti-friction bearings found in a wide variety of automotive, farm, industrial and construction equipment

PROPERTIES

- Provides excellent water resistance and thermal stability under normal conditions
- Adheres well to lubricated parts, sealing them from dirt and abrasive materials
- Enhanced with strawberry scent

TYPE

Lithium soap multipurpose grease

GRADES

NLGI Nos. 2 and 3

AVAILABLE PACKAGES

MP 2

- 400-lb (181-kg) drum
- 35-lb (16-kg) pail

MP 3

- 400-lb (181-kg) drum
- 35-lb (16-kg) pail
- 24 x 1/2 kg in carton
- 6 x 2 kg in carton

TYPICAL CHARACTERISTICS

	MP 2	MP 3
Appearance, Texture	Uniform/Smooth	Unifrom/Smooth
Color, Visual	Red	Red
Worked Pen. at 25°C, 100g, 5 secs., mm/10		
60 strokes	270	232
Dropping Point, °C	195	195
Tilted Wheel Bearing Test		
Slump Rating	Passes	Passes
Leakage in grams	nil	nil
Base oil Viscosity, cSt at 40°C	155	170