

HYDROTUR AW (GT)

DESCRIPTION

HYDROTUR AW (GT) is a highly advanced turbine oil designed to meet the most severe demands of today's gas turbines. It meets the requirements of most gas turbines such as:

- GEC/Alsthom
- Abex-Denison HF-O
- Vickers VM-2950-S
- Cincinnati Milacron P-68, P-69, P-70
- Rexnord
- Commercial Shearing

PROPERTIES

- Contains high performance anti-wear additives for maximum durability and efficiency of equipment
- Exhibits excellent water tolerance and hydrolytic stability preventing rust and corrosion of metal parts

APPLICATIONS

- Recommended for gas turbines
- Can also be used for high speed, high pressure hydraulic circuits containing any combination of pumps operating at maximum output and other turbines and compressor circulating systems

GRADE

- ISO VG 32 and 46

AVAILABLE PACKAGES

- 200-liter drum
- 18-liter pail

TYPICAL CHARACTERISTICS

	32	46
Specific Gravity at 15.6°C	0.8493	0.8735
Appearance	Clear	Clear
Flash Point, COC, °C	220	226
Color, ASTM	1.0	1.0
Viscosity at 40°C, cSt	31.7	45.6
Viscosity at 100°C, cSt	5.59	7.18
Viscosity Index	115	118