

HYDROTUR T

DESCRIPTION

HYDROTUR T is a versatile, circulating oil manufactured from highly refined base oils of turbine grade quality and additives that control rusting, provide additional oxidation stability, inhibit foaming, and exhibit excellent demulsibility.

PROPERTIES

- Meets international standards of oxidation stability, anti-rust property and performance
- Formulations are compatible with sealing materials used in hydraulic systems

TYPE

- Premium quality circulating oil

APPLICATIONS

- Recommended (ISO VG 32, 46 and 68) for steam turbines manufactured by GEC Alsthom, Hitachi/Marubeni, JBE (John Brown Engineering), Mitsui, ABB (Asea Brown Boveri) and Rumania
- Can also be used for turbochargers, compressors, hydraulic systems and plain/anti-friction bearings

GRADES

- ISO VG 32, 46, 68

AVAILABLE PACKAGES

- 200-liter drum
- 18-liter pail

TYPICAL CHARACTERISTICS

	32	46	68
Specific Gravity at 15.6°C	0.8623	0.8686	0.8735
Flash Point, COC, °C	210	218	230
Color, ASTM	0.5	1.0	1.5
Viscosity at 40°C, cSt	31.0	45.0	65.0
Viscosity at 100°C, cSt	5.40	6.80	8.60
Viscosity Index	105	105	105
Pour Point, °C	-9	-9	-9
